



Overview

The **TDD Industrial DP Fanless** Touch Monitors include Rear Mount, Panel Mount, and Closed Frame types, designed for embedded into metal enclosures. Built with Aluminum Die Cast Housing, they provide heat dissipation and mechanical strength. Multi-signal video inputs including HDMI, Display Port, and VGA ensure system compatibility. With industrial Aviation Power Connectors and Phoenix Terminal audio outputs, these monitors deliver performance in environments for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Wall mount / VESA mount design with **Rugged High Bright & Wide Temperature TFT Panel, Sturdy Aluminum Frame & Steel Back**
- IP65 (front) for water and dust protection, flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel

Diagonal Size	10.1"(16:10), 25.65cm, Active matrix TFT LCD (LED)
Active Area (mm)	216.96 mm x 135.6 mm
Resolution	1280 x 800
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 178° total
Number of Colors	16.7 million
Brightness (typical)	400 nits
Response Time-total	25 (Typ.)(Tr+Td) ms
Contrast Ratio	800:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

Touch

Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof; Optional: Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial
Supported OS	Windows / Android / Linux / Mac

Interfaces / Connectors / Controls

Video Interfaces	VGA x1/HDMI (Type A)/DVI x1 (opt.)/Display Port x1 (opt.)/USB-B x1 for Touch ; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC (5.5mmx2.5mm) x1; 5 OSD buttons

Power

Power	Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 10W typical, 1.2W sleep, 0.5W off
Mechanical (Subject to change)	Product Dimensions: 255.02 x 163.56 x 43.8 mm / Weight (Unpacked / Packed): 2.1 / 2.7 kg Box Dimensions: 340 x 290 x 160 mm / VESA Mounting: 75 x 75 mm M4≤6mm VESA

Environmental

Environmental	Operating / Storage Temperature: -20°C to 60°C
---------------	---

Accessories

Accessories	Power adapter / cable, HDMI / VGA / Touch USB cable, wall mount / desktop kits (optional)
-------------	--

Others

Others	MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black grey
--------	---

Ready for Use: 24/7, **Cutout Dimensions: 249.85 x 158.39 mm**

* TDD (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.