


TDD-TPC-CF121WPS

12.1" **Waterproof** **Stainless Steel** Closed Frame PCAP Touch Panel PCs



Overview

The **TDD Touch Panel PCs** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical and Custom** types, deliver a great computing solution when your application requires the PCs to be integrated into equipment. It can withstand harsh industrial environment with multiple I/O & expansion slots, rugged internal components & fanless cooling systems. Powered by Android or Intel with heavy-duty aluminum or steel enclosure, high durability & versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

Features

- Touch thru glass (with **Anti-mist Optical Bonding**) enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged TFT Panel & Easy to Clean Anti-Corrosion 304 Sturdy Stainless Steel Enclosure**
- **IP67 Fully Enclosed Fanless Design with M12 Metal I/O Connectors**, flexible mounting in any table, kiosk or cabinet

Specifications

System

Processor	Android: RK3188/RK3288/RK3566/RK3568 Quad-core Cortex-A9/A17/A55 1.6/1.8/ 2.0GHz Windows: Intel® J1900 / J4125 Quad Core 2.0 / 2.7GHz / Intel® Core™ i3 / i5 / i7 / i9 4-13 th G
Memory(RAM)	Android: 1 / 2GB(std) / 4 / 8 / 16GB; Windows: DDR3/4 2 / 4(std) / 8 / 16 / 32 / 64GB
Storage	Android: 4/8/ 16(std) /32/64GB eMMC Flash; Windows: 32/64(std)/128/256/512GB SSD/HDD

Panel

Size / Active Area (mm)	12.1"(4:3), 30.73cm, Active matrix TFT LCD (LED) / 246 mm x 184.5 mm
Resolution / Contrast	1024 x 768 / 1000:1
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 179° total
Color Depth/Brightness	16.7 million / 1000 nits (Optional: 350 / 500 nits)
Response Time / Freq	25 (Typ.)(Tr+Td) ms / Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

Touch

Touch Technology / OS	PCAP (Projected Capacitive) - 10 Touch Capacity (Optional: Waterproof Firmware)
Surface Treatment	Water, Dust & Vandal proof; Optional : Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial

I / O Ports

Android	USB x2 / COM x2 / LAN x1 / HDMI x1 / DC x1
Windows	USB x2 / COM x2 / LAN x1 / HDMI x1 / DC x1

Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 12.2W typical, 1.2W sleep, 0.5W off

Mechanical

(Subject to change)

Product Dimensions: 302.5 x 242 x 50mm / Weight (Unpacked / Packed): 6.1 / 7.45 kg
Box Dimensions: 400 x 175 x 350mm / VESA Mounting: 100 x 100mm

Environmental

Operating | Storage Temperature / Humidity / IP Level: -20°C to 70°C / 10%-85% / Yes / **IP67**

Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable

Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / silver
Ready for Use: 24/7

* **TDD** (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.