


# TDD-TPC-CF190WPS

19" **Waterproof** **Stainless Steel** Closed Frame PCAP Touch Panel PCs



## Overview

The **TDD Touch Panel PCs** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical and Custom** types, deliver a great computing solution when your application requires the PCs to be integrated into equipment. It can withstand harsh industrial environment with multiple I/O & expansion slots, rugged internal components & fanless cooling systems. Powered by Android or Intel with heavy-duty aluminum or steel enclosure, high durability & versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

## Features

- Touch thru glass (with **Anti-mist Optical Bonding**) enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged TFT Panel & Easy to Clean Anti-Corrosion 304 Sturdy Stainless Steel Enclosure**
- **IP67 Fully Enclosed Fanless Design with M12 Metal I/O Connectors**, flexible mounting in any table, kiosk or cabinet

## Specifications

### System

|             |  |
|-------------|--|
| Processor   | Android: RK3188/RK3288/RK3566/RK3568 Quad-core Cortex-A9/A17/A55 1.6/1.8/ 2.0GHz<br>Windows: Intel® J1900 / J4125 Quad Core 2.0 / 2.7GHz / Intel® Core™ i3 / i5 / i7 / i9 4-13 <sup>th</sup> G |
| Memory(RAM) | Android: 1 / <b>2GB(std)</b> / 4 / 8 / 16GB; Windows: DDR3/4 2 / <b>4(std)</b> / 8 / 16 / 32 / 64GB  |
| Storage     | Android: 4/8/ <b>16(std)</b> /32/64GB eMMC Flash; Windows: 32/64( <b>std</b> )/128/256/512GB SSD/HDD   |

### Panel

|                         |  |
|-------------------------|--|
| Size / Active Area (mm) | 19"(16:9), 48.26cm, Active matrix TFT LCD (LED) / 377.3 mm x 302 mm  |
| Resolution / Contrast   | 1280 x 1024 / 1000:1   |
| Viewing Angle           | Horizontal: 89° or 178° total / Vertical: 89° or 178° total          |
| Color Depth/Brightness  | 16.7 million / <b>1000 nits</b> (Optional: 350 / 500 nits)           |
| Response Time / Freq    | 14 (Typ.)(Tr+Td) ms / Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz |

### Touch

|                       |  |
|-----------------------|--|
| Touch Technology / OS | PCAP (Projected Capacitive) - 10 Touch Capacity ( <b>Optional: Waterproof Firmware</b> )               |
| Surface Treatment     | Water, Dust & Vandal proof; <b>Optional:</b> Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial |

### I / O Ports

|         |  |
|---------|--|
| Android | USB x2 / COM x2 / LAN x1 / HDMI x1 / DC x1 |
| Windows | USB x2 / COM x2 / LAN x1 / HDMI x1 / DC x1 |

### Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 20W typical, 1.2W sleep, 0.5W off

### Mechanical

**(Subject to change)**

Product Dimensions: 449.2 x 374.2x 53.8mm / Weight(Unpacked/Packed): 9.75 / 10.5kg  
Box Dimensions: 475 x 450 x 145mm / VESA Mounting: 100 x 100 / 200 x 200mm

### Environmental

Operating | Storage Temperature / Humidity / IP Level: -20°C to 70°C / 10%-85% / Yes / **IP67**

### Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable

### Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / silver  
Ready for Use: 24/7

\* TDD ([www.tddtouch.com](http://www.tddtouch.com), [sales@tddtouch.com](mailto:sales@tddtouch.com)) reserves the right to change specifications without prior notice.