

TDD-PTM-CF320CT

32" **Industrial** Closed Frame (Desktop / Wall Mount) PCAP Touch Monitors



Overview

The **TDD Touch Monitors** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical** and **Custom** types, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel, flat structure, high durability and versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged TFT Panel, Sturdy Metal Frame & Steel Back**
- IP65 (front) for water and dust protection, flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel

| | |
|-----------------------|---|
| Diagonal Size | 32"(16:9), 81.28cm, Active matrix TFT LCD (LED) |
| Active Area (mm) | 698.4 mm x 392.8 mm |
| Resolution | 1920 x 1080 |
| Viewing Angle | Horizontal: 89° or 178° total / Vertical: 89° or 178° total |
| Number of Colors | 16.7 million |
| Brightness (typical) | 400 nits |
| Response Time-total | 8 (Typ.)(G to G) ms |
| Contrast Ratio | 1200:1 |
| Input Video Frequency | Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz |

Touch

| | |
|-------------------|--|
| Touch Technology | PCAP (Projected Capacitive) - 10 Touch Capacity |
| Surface Treatment | Water, Dust & Vandal proof; Optional: Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial |
| Supported OS | Windows / Android / Linux / Mac |

Interfaces / Connectors / Controls

| | |
|-----------------------|---|
| Video Interfaces | VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes |
| Connectors & Controls | Audio Mini jack x1 / DC x1; 5 OSD buttons |

Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 50W typical, 1.5W sleep, 0.5W off

Mechanical

Product Dimensions: 760.8 x 455.4 x 64.6mm / Weight (Unpacked / Packed): 17 / 21 kg
Box Dimensions: 904 x 575 x 200 mm / VESA Mounting: VESA, MIS-F, 300x300 mm, Y, 6, 90

Environmental

Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C

Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable, wall mount brackets w/screws (opt.)

Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver
Ready for Use: 24/7

* TDD (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.