

# TDD-OFTM-BF104HO

## 10.4" **Outdoor** Bezel-free (Rear Mount) Open Frame PCAP Touch Monitors



### Overview

The **TDD Touch Monitors** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical and Custom** types, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel, flat structure, high durability and versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

### Features

- Touch thru glass (with **AG, UV Filter & Anti-mist Optical Bonding**) enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged High Bright TFT Panel&Auto-dimmer, Sturdy Aluminum Front Frame&Steel Back**
- IP65 (front) for water and **Dust Protection with Smart Fans**, flexible mounting in any table, kiosk, or cabinet design

### Specifications

#### Panel

Diagonal Size 10.4"(4:3), 26.416cm, Active matrix TFT LCD (LED)

Active Area (mm) 211.2 mm x 158.4 mm

Resolution 1024 x 768

Viewing Angle Horizontal: 80° or 160° total / Vertical: 80° or 160° total

Number of Colors 16.7 million

Brightness (typical) **1000 nits**

Response Time-total 20 (Typ.)(Tr/Td) ms

Contrast Ratio 700:1

Input Video Frequency Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

#### Touch

Touch Technology PCAP (Projected Capacitive) - 10 Touch Capacity (**Optional: Waterproof Firmware**)

Surface Treatment Water, Dust & Vandal proof; **Optional:** Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial

Supported OS Windows / Android / Linux / Mac

#### Interfaces / Connectors / Controls

Video Interfaces VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes

Connectors & Controls Audio Mini jack x1 / DC x1; 5 OSD buttons

#### Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 10W typical, 1.2W sleep, 0.5W off

#### Mechanical

Product Dimensions: 264 x 204 x 40mm / Weight (Unpacked / Packed): 3.35 / 3.95 kg  
Box Dimensions: 400 x 160 x 340mm / VESA Mounting: 75 x 75 / 100 x 100mm

#### Environmental

Operating / Storage Temperature: **-20°C to 70°C** / -30°C to 80°C (**except for some models**)

#### Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable, flush mount brackets w/screws (opt.)

#### Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver  
Ready for Use: 24/7

\* TDD ([www.tddtouch.com](http://www.tddtouch.com), [sales@tddtouch.com](mailto:sales@tddtouch.com)) reserves the right to change specifications without prior notice.